



GVPM20KD

O				

Presentation	When the power module is installed, the UPS automatically detects the change. Available as a power module replacement, or for increased capacity for the Scalable Galaxy VS models.
Lead time	Usually Ships within 2 Weeks
Main	
Other Input Voltage	208 V 400 V 480 V
Other Output Voltage	208 V 400 V 480 V
Kw Rating	20000 W
Rated power in VA	20000 VA

Physical

Height	5.12 in (130 mm)
Width	17.01 in (432 mm)
Depth	25.39 in (645 mm)
Net Weight	55.12 lb(US) (25 kg)

Output

Max Configurable Power (Watts) 20000 W

Environmental

Ambient Air Temperature for Operation	32122 °F (050 °C)
Relative Humidity	095 % non-condensing
Operating altitude	09842.52 ft (03000 m)
Ambient Air Temperature for Storage	-13131 °F (-2555 °C)
Storage Relative Humidity	1080 % non-condensing

Ordering and shipping details

GTIN 731304410966

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	12.99 in (330 mm)
Package 1 Width	30.71 in (780 mm)
Package 1 Length	22.83 in (580 mm)
Package 1 Weight	105.82 lb(US) (48 kg)

Offer Sustainability

EU RoHS Directive	Under investigation	
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins	

Recommended replacement(s)