

Disclaimer. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Overview

Presentation	A 50kW (400V or 480V) / 25kW (208V) power module compatible with the Galaxy VS and Galaxy VL 3-
	phase UPS. When the power module is installed, the UPS automatically detects the change. Available as a power module replacement, or for increased capacity for the scalable Galaxy VS models.

Power Module, 50 kW at 400/480V,

Lead time Usually Ships within 2 Weeks

Main

Other Input Voltage	400/480 V
Other Output Voltage	400 V 480 V
Kw Rating	50000 W
Rated power in VA	50000 VA

Physical

Height	5.12 in (130 mm)
Width	17.01 in (432 mm)
Depth	25.39 in (645 mm)
Net Weight	83.78 lb(US) (38 kg)

Output

Max Configurable Power (Watts) 50000 W

Environmental

Ambient Air Temperature for Operation	32122 °F (050 °C)
Relative Humidity	095 % non-condensing
Operating altitude	09842.52 ft (03000 m)
Ambient Air Temperature for Storage	-13131 °F (-2555 °C)
Storage Relative Humidity	1080 % non-condensing

Ordering and shipping details

GTIN 731304410959

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	12.99 in (330 mm)
Package 1 Width	30.71 in (780 mm)
Package 1 Length	22.83 in (580 mm)
Package 1 Weight	136.69 lb(US) (62 kg)

Offer Sustainability

REACh Regulation	REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
China RoHS Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
RoHS exemption information	Yes
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.

Recommended replacement(s)