

# Product data sheet

Specifications



## Galaxy VS UPS 20kW 208V for up to 4 internal 9Ah smart modular battery strings, Start-up 5x8

GVSUPS20K0B4FS

### Overview

**Presentation** Highly efficient, easy-to-deploy 20kW, 208V 3-phase UPS that brings best-in-class power protection and low total cost of ownership to edge, small and medium data centers, as well as to critical infrastructure in commercial and industrial applications. This UPS is for up to 4 smart modular high capacity battery strings, but is supplied without batteries, so you can easily customize the battery runtime. Includes 5x8 start-up service.

**Lead time** Usually Ships within 2 Weeks

### Main

**Main Input Voltage** 208 V 3 phase

**Other Input Voltage** 200 V  
220 V

**Main Output Voltage** 208 V 3 phase

**Other Output Voltage** 200 V  
220 V

**Kw Rating** 20 kW

**Rated power in VA** 20 kVA

**Battery type** Internal modular battery  
VRLA

**Provided equipment** Dust filter  
Installation manual  
Integrated network management  
Start-Up Service  
EcoStruxure Ready

### Batteries & Runtime

**Battery voltage** 480V

**End of Discharge Battery Voltage** 384 V DC

**End of Discharge Maximum Battery Current** 54 A

**Battery power in VAH** 0 VAh runtime

**Extendable Run Time** 0

### General

**Redundant** No

## Physical

Color	White
Height	58.46 in (148.5 cm)
Width	20.51 in (52.1 cm)
Depth	33.35 in (84.7 cm)
Net Weight	440.92 lb(US) (200 kg)
USB compatible	No

## Input

Input Frequency	40 - 70 Hz
Efficiency at full load	177...239 V
Maximum Input Current per Phase	72 A
Maximum Short Circuit Withstand (Icw)	65 kA
Input Total Harmonic Distortion	Less than 3% for full load
Load power factor	From 0.7 leading to 0.7 lagging without any derating
Input Power Factor at Full Load	0.99

## Output

Max Configurable Power (Watts)	20 kW
Harmonic distortion	Less than 5%
Output Frequency (sync to mains)	50 Hz sync to mains 60 Hz sync to mains
Crest factor	2.5
Waveform Type	Sine wave
Output voltage tolerance	+/-1% after 50ms
Output Voltage THD	< 2% linear load and < 5% non-linear load
Overload Operation	10 minutes @ 125% and 60 seconds @ 150%
Bypass type	Built-in Static Bypass
Maximum configurable power in VA	20 kVA

## Conformance

Standards	CSA C22.2 No 107.3 FCC Part 15 class A IEC 62040-1-1 IEC 62040-2 IEC 62040-3 UL 1778 5th edition OSHDP
-----------	--

## Environmental

Ambient air temperature for operation	32...104 °F (0...40 °C)
Relative Humidity	0...95 % non-condensing
Operating altitude	0...3300 ft
Ambient Air Temperature for Storage	5...104 °F (-15...40 °C)

<b>Storage Relative Humidity</b>	10...80 % non-condensing
<b>Storage altitude</b>	0...10000 ft (0.00...3048.00 m)
<b>Acoustic level</b>	61 dBA
<b>Heat dissipation</b>	4356 Btu/h
<b>IP degree of protection</b>	IP20

## Communications & Management

<b>Control panel</b>	Touch Screen LCD User Interface
----------------------	---------------------------------

## Ordering and shipping details

<b>GTIN</b>	731304409786
-------------	--------------

## Packing Units

<b>Unit Type of Package 1</b>	PCE
<b>Number of Units in Package 1</b>	1
<b>Package 1 Height</b>	66.14 in (168 cm)
<b>Package 1 Width</b>	38.98 in (99 cm)
<b>Package 1 Length</b>	25.20 in (64 cm)
<b>Package 1 Weight</b>	440.92 lb(US) (200 kg)

## Offer Sustainability

<b>Sustainable offer status</b>	Green Premium product
<b>REACH Regulation</b>	<a href="#">REACH Declaration</a>
<b>EU RoHS Directive</b>	Compliant <a href="#">EU RoHS Declaration</a>
<b>Mercury free</b>	Yes
<b>China RoHS Regulation</b>	<a href="#">China RoHS declaration</a>
<b>RoHS exemption information</b>	Yes
<b>Environmental Disclosure</b>	<a href="#">Product Environmental Profile</a>
<b>Circularity Profile</b>	<a href="#">End of Life Information</a>
<b>Optimized Energy Efficiency</b>	Energy efficient product
<b>Take-back</b>	Take-back program available

## Contractual warranty

<b>Warranty</b>	1 year on-site repair or replace with factory authorized Start-Up
-----------------	---

## Recommended replacement(s)