

Product data sheet

Specifications



Galaxy VS UPS 25kW 208V, 2 internal 9Ah smart modular battery strings, expandable to 4, Start-up 5x8

GVSUPS25KB4FS

Overview

Presentation Highly efficient, easy-to-deploy 25kW, 208V 3-phase UPS that brings best-in-class power protection and low total cost of ownership to edge, small and medium data centers, as well as to critical infrastructure in commercial and industrial applications. Includes 5x8 start-up service and 2 smart high-capacity modular battery strings, expandable to 4 strings for extended runtime. Runtime charts available in the Documents tab.

Lead time Usually Ships within 2 Weeks

Main

Main Input Voltage 208 V 3 phase

Other Input Voltage 200 V
220 V

Main Output Voltage 208 V 3 phase

Other Output Voltage 200 V
220 V

Kw Rating 25 kW

Rated power in VA 25 kVA

Battery type Internal modular battery
VRLA

Provided equipment Battery modules ship installed
Dust filter
EcoStruxure IT ready (UPS)
Installation guide
Integrated network management
Power modules ship installed
Start-Up Service

Batteries & Runtime

Battery voltage 480V

End of Discharge Battery Voltage 384 V DC

End of Discharge Maximum Battery Current 68 A

Battery power in VAH 0 VAh runtime

Extendable Run Time 0

General

Bypass Voltage Tolerance +/- 10 %

Redundant No

Physical

Color	White
Height	58.46 in (148.5 cm)
Width	20.51 in (52.1 cm)
Depth	33.35 in (84.7 cm)
Net Weight	1014.13 lb(US) (460 kg)
USB compatible	No

Input

Input Frequency	40 - 70 Hz
Efficiency at full load	177...239 V 208 V
Maximum Input Current per Phase	90 A
Maximum Short Circuit Withstand (Icw)	65 kA
Input Total Harmonic Distortion	Less than 3% for full load
Load power factor	From 0.7 leading to 0.7 lagging without any derating
Input Power Factor at Full Load	0.99

Output

Max Configurable Power (Watts)	25 kW
Harmonic distortion	Less than 5%
Output Frequency (sync to mains)	50 Hz sync to mains 60 Hz sync to mains 50 Hz +/- 0.1 % for 50 Hz nominal not synced 60 Hz +/- 0.1 % for 60 Hz nominal not synced
Crest factor	2.5
Waveform Type	Sine wave
Output voltage tolerance	+/-1% after 50ms
Overload Operation	10 minutes @ 125% and 60 seconds @ 150%
Bypass type	Built-in Static Bypass
Maximum configurable power in VA	25 kVA

Conformance

Standards	CSA C22.2 No 107.3 FCC Part 15 class A IEC 62040-3 IEC 60721-4-2 Level 2M2 UL 1778 5th edition
-----------	--

Environmental

Ambient air temperature for operation	32...104 °F (0...40 °C)
Relative Humidity	0...95 % non-condensing
Operating altitude	0...3281 ft
Ambient Air Temperature for Storage	5...104 °F (-15...40 °C)
Storage Relative Humidity	10...80 % non-condensing

Storage altitude	0...10000 ft (0.00...3048.00 m)
Acoustic level	61 dBA
Heat dissipation	5950 Btu/h
IP degree of protection	IP20

Communications & Management

Free slots	1
Control panel	Touch Screen LCD User Interface

Ordering and shipping details

GTIN	731304641759
------	--------------

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	66.14 in (168 cm)
Package 1 Width	38.98 in (99 cm)
Package 1 Length	25.20 in (64 cm)
Package 1 Weight	1080.27 lb(US) (490 kg)

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information
Optimized Energy Efficiency	Energy efficient product
Take-back	Take-back program available

Contractual warranty

Warranty	1 year on-site repair or replace with factory authorized Start-Up
----------	---

Recommended replacement(s)