

Product data sheet

Specifications



Galaxy VS UPS 30kW 480V with N+1 power module for external batteries, Start-up 5x8

GVSUPS30KRG5

Overview

Presentation Highly efficient, easy-to-deploy 30kW, 480V 3-phase UPS that brings best-in-class power protection and low total cost of ownership to edge, small and medium data centers, as well as to critical infrastructure in commercial and industrial applications. Includes 5x8 start-up service and one additional power module for N+1 redundancy.

Lead time Usually Ships within 2 Weeks

Main

Main Input Voltage 480 V 3 phase

Main Output Voltage 480 V 3 phase

Kw Rating 30 kW

Rated power in VA 30 kVA

Battery type External battery system
Li-Ion (Lithium Ion)
VRLA

Provided equipment Dust filter
EcoStruxure IT ready (UPS)
Installation guide
Integrated network management
Power modules ship installed
Start-Up Service

Batteries & Runtime

Battery voltage 384-576VDC

End of Discharge Battery Voltage 307 V DC

End of Discharge Maximum Battery Current 101 A

General

Bypass Voltage Tolerance +/- 10 %

Redundant Yes

Physical

Color White

Height 58.46 in (148.5 cm)

Width 20.51 in (52.1 cm)

Depth 33.35 in (84.7 cm)

Net Weight	551.16 lb(US) (250 kg)
------------	------------------------

Input

Input Frequency	40 - 70 Hz
Efficiency at full load	408...552 V 480 V
Maximum Input Current per Phase	45 A
Maximum Short Circuit Withstand (Icw)	65 kA
Input Total Harmonic Distortion	Less than 5% for full load
Load power factor	From 0.7 leading to 0.7 lagging without any derating

Output

Max Configurable Power (Watts)	30 kW
Output Frequency (sync to mains)	50 Hz sync to mains 60 Hz sync to mains 50 Hz +/- 0.1 % for 50 Hz nominal not synced 60 Hz +/- 0.1 % for 60 Hz nominal not synced
Crest factor	2.5
Waveform Type	Sine wave
Output voltage tolerance	+/-1% after 50ms
Output Voltage THD	< 1% linear load and < 5% non-linear load
Overload Operation	10 minutes @ 125% and 60 seconds @ 150%
Bypass type	Built-in Static Bypass
Maximum configurable power in VA	30 kVA

Conformance

Standards	IEC 62040-1-1 IEC 62040-2 UL 1778 5th edition FCC Part 15 class A IEC 60721-4-2 Level 2M2 UL 924 Listed
-----------	--

Environmental

Ambient air temperature for operation	32...104 °F (0...40 °C)
Relative Humidity	0...95 % non-condensing
Operating altitude	0...3300 ft
Ambient Air Temperature for Storage	-13...131 °F (-25...55 °C)
Storage Relative Humidity	10...80 % non-condensing
Acoustic level	64 dBA
Heat dissipation	2922 Btu/h
IP degree of protection	IP21

Communications & Management

Control panel	Touch Screen LCD User Interface
---------------	---------------------------------

Ordering and shipping details

GTIN 731304418481

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	58.46 in (148.5 cm)
Package 1 Width	20.51 in (52.1 cm)
Package 1 Length	33.35 in (84.7 cm)
Package 1 Weight	551.16 lb(US) (250 kg)

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
China RoHS Regulation	China RoHS declaration
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information
Optimized Energy Efficiency	Energy efficient product
Take-back	Take-back program available

Contractual warranty

Warranty 1 year on-site repair or replace with factory authorized Start-Up

Recommended replacement(s)