

# Product data sheet

Specifications



## Galaxy VS 60kW 208V for external batteries, Start-up 5x8

GVSUPS60KFS

### Overview

**Presentation** Highly efficient, easy-to-deploy 60kW, 208V 3-phase UPS that brings best-in-class power protection and low total cost of ownership to edge, small and medium data centers, as well as to critical infrastructure in commercial and industrial applications. Includes 5x8 start-up service.

**Lead time** Usually Ships within 2 Weeks

### Main

**Main Input Voltage** 208 V 3 phase

**Other Input Voltage** 200 V  
220 V

**Main Output Voltage** 208 V

**Kw Rating** 60 kW

**Rated power in VA** 60 kVA

**Battery type** External battery system  
Li-Ion (Lithium Ion)  
VRLA

**Provided equipment** Dust filter  
EcoStruxure IT ready (UPS)  
Installation guide  
Integrated network management  
Power modules ship installed  
Start-Up Service

### Batteries & Runtime

**Battery voltage** 384-480VDC

**End of Discharge Battery Voltage** 307 V DC

**End of Discharge Maximum Battery Current** 204 A

### General

**Bypass Voltage Tolerance** +/- 10 %

**Redundant** No

### Physical

**Color** White

**Height** 58.46 in (148.5 cm)

**Width** 20.51 in (52.1 cm)

Depth	33.35 in (84.7 cm)
Net Weight	612.89 lb(US) (278 kg)

## Input

Input Frequency	40 - 70 Hz
Efficiency at full load	177...239 V 208 V
Maximum Input Current per Phase	215 A
Maximum Short Circuit Withstand (I <sub>cw</sub> )	65 kA
Input Total Harmonic Distortion	Less than 5% for full load
Load power factor	From 0.7 leading to 0.7 lagging without any derating

## Output

Max Configurable Power (Watts)	60 kW
Output Frequency (sync to mains)	50 Hz sync to mains 60 Hz sync to mains 50 Hz +/- 0.1 % for 50 Hz nominal not synced 60 Hz +/- 0.1 % for 60 Hz nominal not synced
Crest factor	2.5
Waveform Type	Sine wave
Output voltage tolerance	+/-1% after 50ms
Overload Operation	10 minutes @ 125% and 60 seconds @ 150%
Bypass type	Built-in Static Bypass
Maximum configurable power in VA	60 kVA

## Conformance

Standards	IEC 62040-1-1 IEC 62040-2 UL 1778 5th edition FCC Part 15 class A IEC 60721-4-2 Level 2M2 UL 924 Listed
-----------	--

## Environmental

Ambient air temperature for operation	32...104 °F (0...40 °C)
Relative Humidity	0...95 % non-condensing
Operating altitude	0...3300 ft
Ambient Air Temperature for Storage	-13...131 °F (-25...55 °C)
Storage Relative Humidity	10...80 % non-condensing
Acoustic level	68 dBA
Heat dissipation	10974 Btu/h
IP degree of protection	IP21

## Communications & Management

Control panel	Touch Screen LCD User Interface
---------------	---------------------------------

## Ordering and shipping details

---

GTIN 731304418450

## Packing Units

---

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	66.14 in (168 cm)
Package 1 Width	38.98 in (99 cm)
Package 1 Length	25.20 in (64 cm)
Package 1 Weight	694.46 lb(US) (315 kg)

## Offer Sustainability

---

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
China RoHS Regulation	<a href="#">China RoHS declaration</a>
RoHS exemption information	Yes
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
Circularity Profile	<a href="#">End of Life Information</a>
Optimized Energy Efficiency	Energy efficient product
Take-back	Take-back program available

## Contractual warranty

---

Warranty 1 year on-site repair or replace with factory authorized Start-Up

## Recommended replacement(s)