

# Product data sheet

Specifications



## Galaxy VS UPS 80kW 400V for up to 5 internal 9Ah smart modular battery strings, Start-up 5x8

GVSUPS80K0B5HS

### Overview

**Presentation** Highly efficient, easy-to-deploy 80kW, 400V 3-phase UPS that brings best-in-class power protection and low total cost of ownership to edge, small and medium data centers, as well as to critical infrastructure in commercial and industrial applications. This UPS is for up to 5 smart modular high capacity battery strings, but is supplied without batteries, so you can easily customize the battery runtime. Includes 5x8 start-up service.

**Lead time** Usually Ships within 2 Weeks

### Main

**Main Input Voltage** 400 V 3 phase

**Other Input Voltage** 380 V  
415 V

**Main Output Voltage** 400 V 3 phase

**Other Output Voltage** 380 V  
415 V

**Kw Rating** 80 kW

**Rated power in VA** 80 kVA

**Battery type** Internal modular battery  
VRLA

**Provided equipment** Dust filter  
Installation manual  
Integrated network management  
Start-Up Service  
EcoStruxure Ready

### Batteries & Runtime

**Battery voltage** 480V

**End of Discharge Battery Voltage** 384 V

**End of Discharge Maximum Battery Current** 217 A

**Battery power in VAH** 0 VAh runtime

**Extendable Run Time** 0

### General

**Redundant** No

## Physical

Color	White
Height	77.56 in (197 cm)
Width	21.65 in (55 cm)
Depth	33.35 in (84.7 cm)
Net Weight	652.57 lb(US) (296 kg)
USB compatible	No

## Input

Input Frequency	40 - 70 Hz
Efficiency at full load	340...460 V 400 V
Maximum Input Current per Phase	144 A
Maximum Short Circuit Withstand (Icw)	65 kA
Input Total Harmonic Distortion	Less than 3% for full load
Load power factor	From 0.7 leading to 0.7 lagging without any derating
Input Power Factor at Full Load	0.99

## Output

Max Configurable Power (Watts)	80 kW
Harmonic distortion	Less than 3%
Output Frequency (sync to mains)	50 Hz sync to mains 60 Hz sync to mains
Crest factor	2.5
Waveform Type	Sine wave
Output voltage tolerance	+/- 5% after 2ms +/-1% after 50ms
Output Voltage THD	< 1% linear load and < 3% non-linear load
Overload Operation	10 minutes @ 125% and 60 seconds @ 150%
Bypass type	Built-in Static Bypass
Maximum configurable power in VA	80 kVA

## Conformance

Standards	IEC 62040-1-1 IEC 62040-2 OSHPD
-----------	---------------------------------------

## Environmental

Ambient air temperature for operation	32...104 °F (0...40 °C)
Relative Humidity	0...95 % non-condensing
Operating altitude	0...3300 ft
Ambient Air Temperature for Storage	5...104 °F (-15...40 °C)
Storage Relative Humidity	10...80 % non-condensing
Storage altitude	0...10000 ft (0.00...3048.00 m)

Acoustic level	65 dBA
Heat dissipation	9263 Btu/h
IP degree of protection	IP20

## Communications & Management

Control panel	Touch Screen LCD User Interface
---------------	---------------------------------

## Ordering and shipping details

GTIN	731304410096
------	--------------

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	81.97 in (208.2 cm)
Package 1 Width	39.76 in (101 cm)
Package 1 Length	29.72 in (75.5 cm)
Package 1 Weight	551.16 lb(US) (250 kg)

## Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
China RoHS Regulation	<a href="#">China RoHS declaration</a>
RoHS exemption information	Yes
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
Circularity Profile	<a href="#">End of Life Information</a>
Optimized Energy Efficiency	Energy efficient product
Take-back	Take-back program available

## Contractual warranty

Warranty	1 year on-site repair or replace with factory authorized Start-Up
----------	---

## Recommended replacement(s)