

Product data sheet

Specifications



Galaxy VS UPS 80kW 400V for external batteries, halogen-free cables, marine certified, Start-up 5x8

GVSUPS80KMHS

Overview

Presentation	Highly efficient, easy-to-deploy 80kW, 400V 3-phase UPS that brings best-in-class power protection and low total cost of ownership to edge, small and medium data centers, as well as to critical infrastructure in commercial and industrial applications. Includes 5x8 start-up service and halogen-free cables. Marine certified.
Lead time	Usually Ships within 2 Weeks

Main

Main Input Voltage	400 V 3 phase
Other Input Voltage	380 V 415 V
Main Output Voltage	400 V 3 phase
Kw Rating	80 kW
Rated power in VA	80 kVA
Battery type	External battery system Li-Ion (Lithium Ion) VRLA
Provided equipment	Dust filter EcoStruxure IT ready (UPS) Installation guide Integrated network management Power modules ship installed Start-Up Service

Batteries & Runtime

Battery voltage	384-576VDC
End of Discharge Battery Voltage	307 V DC
End of Discharge Maximum Battery Current	217 A
Battery power in VAH	0 VAh runtime
Extendable Run Time	0

General

Bypass Voltage Tolerance	+/- 10 %
Redundant	No

Physical

Color	White
Height	58.46 in (148.5 cm)
Width	2.05 in (52.1 mm)
Depth	33.35 in (84.7 cm)
Net Weight	551.16 lb(US) (250 kg)
USB compatible	No

Input

Input Frequency	40 - 70 Hz
Efficiency at full load	340...460 V 400 V
Maximum Input Current per Phase	144 A
Maximum Short Circuit Withstand (Icw)	65 kA
Input Total Harmonic Distortion	Less than 3% for full load
Load power factor	From 0.7 leading to 0.7 lagging without any derating

Output

Max Configurable Power (Watts)	80 kW
Output Frequency (sync to mains)	50 Hz sync to mains 60 Hz sync to mains 50 Hz +/- 0.1 % for 50 Hz nominal not synced 60 Hz +/- 0.1 % for 60 Hz nominal not synced
Crest factor	2.5
Waveform Type	Sine wave
Output voltage tolerance	+/-1% after 50ms
Output Voltage THD	< 1% linear load and < 5% non-linear load
Overload Operation	10 minutes @ 125% and 60 seconds @ 150%
Bypass type	Built-in Static Bypass
Maximum configurable power in VA	80 kVA

Conformance

Standards	EN/IEC 62040-1 EN/IEC 62040-2 FCC Part 15 class A IEC 60721-4-2 Level 2M2 UL 1778 5th edition
-----------	---

Environmental

Ambient air temperature for operation	32...104 °F (0...40 °C)
Relative Humidity	0...95 % non-condensing
Operating altitude	0...3300 ft
Ambient Air Temperature for Storage	-13...131 °F (-25...55 °C)
Storage Relative Humidity	10...80 % non-condensing
Acoustic level	68 dBA

Heat dissipation	8394 Btu/h
IP degree of protection	IP21

Communications & Management

Control panel	Touch Screen LCD User Interface
---------------	---------------------------------

Ordering and shipping details

GTIN	731304418382
------	--------------

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	66.14 in (168 cm)
Package 1 Width	38.98 in (99 cm)
Package 1 Length	25.20 in (64 cm)
Package 1 Weight	639.34 lb(US) (290 kg)

Offer Sustainability

REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
China RoHS Regulation	China RoHS declaration
RoHS exemption information	Yes

Contractual warranty

Warranty	1 year on-site repair or replace with factory authorized Start-Up
----------	---

Recommended replacement(s)