

Product data sheet

Specifications



APC Smart-UPS SRT Tower Isolation/Step-Down Transformer, 5kVA, 8x 5-20R & 2x L6-20R & 1x L6-30R & 1x L14-30R NEMA outlets

SRT5KTF

Product availability : Stock - Normally stocked in distribution facility

Overview

Lead time Usually in Stock

Main

Main Input Voltage 208 V
240 V

Main Output Voltage 120 V
208 V

Other Output Voltage 240 V

Input Connection Type NEMA L6-30P

Cable length 3 ft (0.91 m)

Number of cables 1

Provided Equipment User Manual

Physical

Color Black

Height 17.01 in (43.2 cm)

Width 5.12 in (13 cm)

Depth 25.98 in (66 cm)

Net Weight 125.00 lb(US) (56.7 kg)

Mounting preference No preference

Mounting Mode Rack-mounted with kit

Input

Input Frequency 50/60 Hz

Output

Maximum Total Current Draw per Phase 5000 A

Number of power socket outlets 12

8 NEMA 5-20R
2 NEMA L6-20R
1 NEMA L6-30R

Environmental

Ambient air temperature for operation	32...104 °F (0...40 °C)
Relative Humidity	0...95 % non-condensing
Operating altitude	0...10000 ft
Ambient Air Temperature for Storage	5...113 °F (-15...45 °C)
Storage Relative Humidity	0...95 % non-condensing
Storage altitude	0...50000 ft (0.00...15240.00 m)

Ordering and shipping details

Category	80230-IG SEBA TO SEUSA
Discount Schedule	BMS1
GTIN	731304318873
Returnability	No
Country of origin	US

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	13.66 in (34.7 cm)
Package 1 Width	38.58 in (98 cm)
Package 1 Length	23.74 in (60.3 cm)
Package 1 Weight	139.99 lb(US) (63.5 kg)

Offer Sustainability

REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.
Take-back	Take-back program available

Contractual warranty

Warranty	2 years repair or replace
----------	---------------------------

Recommended replacement(s)