

Product data sheet

Specifications



APC Service Bypass Unit for SRYL, 200/208/230/240V, 125A, MBB, Hardwire Input/Output

SRYLSBP20KP

Overview

Lead time Usually in Stock

Physical

Color Black and silver

Height 6.89 in (175 mm)

Width 17.01 in (432 mm)

Depth 29.72 in (755 mm)

Net Weight 50.71 lb(US) (23 kg)

Mounting Mode Rack-mounted

Input

Max line current 125 A

Environmental

Ambient air temperature for operation 32...104 °F (0...40 °C)

Operating altitude 0...9842.52 ft (0...3000 m)

Ambient Air Temperature for Storage -22...158 °F (-30...70 °C)

Storage altitude 0.00...49212.60 ft (0...15000 m)

Ordering and shipping details

GTIN 731304434702

Packing Units

Unit Type of Package 1 PCE

Number of Units in Package 1 1

Package 1 Height 11.81 in (30 cm)

Package 1 Width 22.83 in (58 cm)

Package 1 Length 38.19 in (97 cm)

Package 1 Weight 71.65 lb(US) (32.5 kg)

Offer Sustainability

REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Mercury free	Yes
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information.
RoHS exemption information	Yes

Contractual warranty

Warranty	2 years
----------	---------

Recommended replacement(s)