

Product data sheet

Specifications



APC Smart-UPS On-Line, 10kVA/10kW, Rackmount 6U, 208V, 6x L6-30R NEMA outlets, Network Card+SmartSlot, Extended runtime, W/ rail kit

SRT10KRMXLT30

Overview

Lead time Usually in Stock

Main

Main Input Voltage	208 V
Other Input Voltage	240 V
Main Output Voltage	208 V
Other Output Voltage	240 V
Kw Rating	10000 W
Rated power in VA	10000 VA
Output connection type	6 NEMA L6-30R
Output connector type	Hard Wire 3-wire (2PH + G) 1
Number of rack unit	6U
Battery type	Lead-Acid battery
Provided equipment	CD with software Documentation CD Installation guide Rack mounting hardware Rack Mounting brackets Rack Mounting support rails Temperature Probe USB cable Warranty card Web/SNMP Management Card

Batteries & Runtime

Included Battery Modules	0
Typical recharge time	1.5 h
RBC Quantity	2
Battery voltage	+/-192 V (split battery referenced to neutral)
Battery Charge Power (Watts)	1191 W rated
Battery power in VAh	1799 VAh runtime
Battery Life	3...5 year(s)
Replacement battery	APCRBC140
	SRT192BP2US

Battery option	SRT192RMBP2 1 3598 VAh SRT192RMBP2 2 5397 VAh SRT192RMBP2 3 7196 VAh SRT192RMBP2 4 8995 VAh SRT192RMBP2 5 10794 VAh SRT192RMBP2 6 12593 VAh SRT192RMBP2 8 16191 VAh SRT192RMBP2 10 19789 VAh
-----------------------	---

Extendable Run Time	1
----------------------------	---

General

Product web sub-family	High density
-------------------------------	--------------

Number of power module free slots	0
--	---

Number of power module filled slots	0
--	---

Redundant	No
------------------	----

Physical

Color	Black
--------------	-------

Height	10.35 in (26.3 cm)
---------------	--------------------

Width	17.01 in (43.2 cm)
--------------	--------------------

Depth	28.15 in (71.5 cm)
--------------	--------------------

Net Weight	245.99 lb(US) (111.58 kg)
-------------------	---------------------------

Mounting Location	Front
--------------------------	-------

Mounting preference	No preference
----------------------------	---------------

Mounting Mode	Rack-mounted
----------------------	--------------

Two post mountable	0
---------------------------	---

USB compatible	Yes
-----------------------	-----

Input

Input Frequency	40 - 70 Hz auto-sensing
------------------------	-------------------------

Number of input connectors	1 Hard Wire 3-wire (2PH + G)
-----------------------------------	------------------------------

Efficiency at full load	100...275 V adjustable (half load)
--------------------------------	------------------------------------

Output

Max Configurable Power (Watts)	10000 W
---------------------------------------	---------

Harmonic distortion	Less than 2%
----------------------------	--------------

Output Frequency (sync to mains)	50/60 Hz +/- 3 Hz sync to mains
---	---------------------------------

Crest factor	3 : 1
---------------------	-------

Topology	Double Conversion Online
-----------------	--------------------------

Waveform Type	Sine wave
----------------------	-----------

Bypass type	Internal Bypass (Automatic and Manual)
--------------------	--

Maximum configurable power in VA	10000 VA
---	----------

Conformance

Product Certifications	ENERGY STAR V2.0 (USA) FCC part 15 class A
-------------------------------	---

Environmental

Ambient air temperature for operation	32...104 °F (0...40 °C)
Relative Humidity	0...95 % non-condensing
Operating altitude	0...10000 ft
Ambient Air Temperature for Storage	5...113 °F (-15...45 °C)
Storage Relative Humidity	0...95 % non-condensing
Storage altitude	0...50000 ft (0.00...15240.00 m)
Acoustic level	55 dBA
Heat dissipation	2490 Btu/h
IP degree of protection	IP20

Communications & Management

Free slots	1
Pre-Installed SmartSlot™ Cards	Network management card 3 with environmental monitoring
Alarm	Audible and visible alarms : prioritized by severity
Emergency Power Off (EPO)	Yes

Surge Protection and Filtering

Surge energy rating	480 J
---------------------	-------


Ordering and shipping details

GTIN	731304732914
------	--------------

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	26.81 in (68.1 cm)
Package 1 Width	39.37 in (100 cm)
Package 1 Length	23.62 in (60 cm)
Package 1 Weight	291.19 lb(US) (132.08 kg)

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
ENERGY STAR®	ENERGY STAR UPS V2.0 (USA) 
REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile

Circularity Profile	End of Life Information
Optimized Energy Efficiency	Energy efficient product
Take-back	Take-back program available

Contractual warranty

Warranty	3 years repair or replace (excluding battery) and 2 years for battery
-----------------	---

Recommended replacement(s)