

# Product data sheet

Specifications



## APC Smart-UPS On-Line, 10kVA/10kW, Tower, 208V, 6x L6-30R NEMA outlets, Network Card+SmartSlot, Extended runtime, W/O rail kit

SRT10KXLT30

### Overview

Lead time Usually in Stock

### Main

Main Input Voltage	208 V
Other Input Voltage	240 V
Main Output Voltage	208 V
Other Output Voltage	240 V
Kw Rating	10000 W
Rated power in VA	10000 VA
Output connection type	6 NEMA L6-30R
Output connector type	Hard Wire 3-wire (2PH + G) 1
Battery type	Lead-Acid battery
Provided equipment	CD with software Documentation CD Installation guide Temperature Probe USB cable Warranty card Web/SNMP Management Card

### Batteries & Runtime

Included Battery Modules	0
Typical recharge time	1.5 h
RBC Quantity	2
Battery voltage	+/-192 V (split battery referenced to neutral)
Battery Charge Power (Watts)	1191 W rated
Battery power in VAh	1799 VAh runtime
Battery Life	3...5 year(s)
Replacement battery	<a href="#">APCRBC140</a> <a href="#">SRT192BP2US</a> <a href="#">SRT192RMBPUS</a>
Battery option	SRT192BP2 1 3598 VAh SRT192BP2 2 5397 VAh

SRT192BP2 3 7196 VAh  
SRT192BP2 4 8995 VAh  
SRT192BP2 5 10794 VAh  
SRT192BP2 6 12593 VAh  
SRT192BP2 8 16191 VAh  
SRT192BP2 10 19789 VAh

---

<b>Extendable Run Time</b>	1
----------------------------	---

## General

---

<b>Product web sub-family</b>	High density
-------------------------------	--------------

---

<b>Number of power module free slots</b>	0
--	---

---

<b>Number of power module filled slots</b>	0
--	---

---

<b>Redundant</b>	No
------------------	----

## Physical

---

<b>Color</b>	Black
--------------	-------

---

<b>Height</b>	17.01 in (43.2 cm)
---------------	--------------------

---

<b>Width</b>	10.35 in (26.3 cm)
--------------	--------------------

---

<b>Depth</b>	28.15 in (71.5 cm)
--------------	--------------------

---

<b>Net Weight</b>	245.99 lb(US) (111.58 kg)
-------------------	---------------------------

---

<b>Mounting Location</b>	Front
--------------------------	-------

---

<b>Mounting preference</b>	No preference
----------------------------	---------------

---

<b>Mounting Mode</b>	Rack-mounted with kit
----------------------	-----------------------

---

<b>Two post mountable</b>	0
---------------------------	---

---

<b>USB compatible</b>	Yes
-----------------------	-----

## Input

---

<b>Input Frequency</b>	40 - 70 Hz auto-sensing
------------------------	-------------------------

---

<b>Number of input connectors</b>	1 Hard Wire 3-wire (2PH + G)
-----------------------------------	------------------------------

---

<b>Efficiency at full load</b>	100...275 V adjustable (half load)
--------------------------------	------------------------------------

## Output

---

<b>Max Configurable Power (Watts)</b>	10000 W
---------------------------------------	---------

---

<b>Harmonic distortion</b>	Less than 2%
----------------------------	--------------

---

<b>Output Frequency (sync to mains)</b>	50/60 Hz +/- 3 Hz sync to mains
---	---------------------------------

---

<b>Crest factor</b>	3 : 1
---------------------	-------

---

<b>Topology</b>	Double Conversion Online
-----------------	--------------------------

---

<b>Waveform Type</b>	Sine wave
----------------------	-----------

---

<b>Bypass type</b>	Internal Bypass (Automatic and Manual)
--------------------	--

---

<b>Maximum configurable power in VA</b>	10000 VA
---	----------

## Conformance

---

<b>Product Certifications</b>	ENERGY STAR V2.0 (USA) FCC part 15 class A NOM UL 1778
-------------------------------	---

## Environmental

Ambient air temperature for operation	32...104 °F (0...40 °C)
Relative Humidity	0...95 % non-condensing
Operating altitude	0...10000 ft
Ambient Air Temperature for Storage	5...113 °F (-15...45 °C)
Storage Relative Humidity	0...95 % non-condensing
Storage altitude	0...50000 ft (0.00...15240.00 m)
Acoustic level	55 dBA
Heat dissipation	2490 Btu/h
IP degree of protection	IP20

## Communications & Management

Free slots	1
Pre-Installed SmartSlot™ Cards	Network management card 3 with environmental monitoring
Alarm	Audible and visible alarms : prioritized by severity
Emergency Power Off (EPO)	Yes

## Surge Protection and Filtering

Surge energy rating	480 J
---------------------	-------


## Ordering and shipping details

GTIN	731304732938
------	--------------

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	26.81 in (68.1 cm)
Package 1 Width	39.37 in (100 cm)
Package 1 Length	23.62 in (60 cm)
Package 1 Weight	284.79 lb(US) (129.18 kg)

## Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a>
ENERGY STAR®	<a href="#">ENERGY STAR UPS V2.0 (USA)</a> 
REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
Circularity Profile	<a href="#">End of Life Information</a>

---

<b>Optimized Energy Efficiency</b>	Energy efficient product
------------------------------------	--------------------------

---

<b>Take-back</b>	Take-back program available
------------------	-----------------------------

---

## **Contractual warranty**

---

<b>Warranty</b>	3 years repair or replace (excluding battery) and 2 years for battery
-----------------	---

**Recommended replacement(s)**