

Product data sheet

Specifications



APC Smart-UPS RT 15kVA, 208V, LCD, rackmount, 14U, 12x 5-20R & 4x L6-20R & 1x L6-30R NEMA outlets, w/transfo 208V to 120V

SURT15KRMXLT-TF5

Overview

Lead time Usually Ships within 2 Weeks

Main

Main Input Voltage	208 V
Main Output Voltage	120 V 208 V
Kw Rating	12000 W
Rated power in VA	15000 VA
Output connection type	12 NEMA 5-20R 4 NEMA L6-20R 1 NEMA L6-30R
Output connector type	Hard Wire 3-wire (2PH + G) 1
Number of rack unit	14U
Battery type	Lead-Acid battery
Provided equipment	CD with software Rack Mounting support rails Smart UPS signalling RS-232 cable User Manual Web/SNMP Management Card

Batteries & Runtime

Included Battery Modules	4
Battery Slots Empty	0
Typical recharge time	2.5 h
RBC Quantity	4
Additional information	Configurable for 220 : 230 or 240 nominal output voltage
Battery voltage	+/-192 V (split battery referenced to neutral)
End of Discharge Battery Voltage	+/-154 V
Battery Charge Power (Watts)	1530 W rated
Battery power in VAH	3840 VAh runtime
Battery Life	3...5 year(s)
Replacement battery	APCRBC140
Battery option	SURT192RMXLBP2 1 7680 VAh SURT192RMXLBP2 2 11520 VAh

SURT192RMXLBP2 3 15360 VAh
 SURT192RMXLBP2 4 19200 VAh
 SURT192RMXLBP2 5 23040 VAh
 SURT192RMXLBP2 6 26880 VAh
 SURT192RMXLBP2 7 30720 VAh
 SURT192RMXLBP2 9 38400 VAh

Extendable Run Time	1
---------------------	---

General

Number of power module free slots	0
-----------------------------------	---

Number of power module filled slots	0
-------------------------------------	---

Redundant	No
-----------	----

Physical

Color	Black
-------	-------

Height	24.49 in (62.2 cm)
--------	--------------------

Width	17.01 in (43.2 cm)
-------	--------------------

Depth	30.43 in (77.3 cm)
-------	--------------------

Net Weight	641.35 lb(US) (290.91 kg)
------------	---------------------------

Mounting Location	Front
-------------------	-------

Mounting preference	Lower
---------------------	-------

Mounting Mode	Rack-mounted
---------------	--------------

Two post mountable	0
--------------------	---

USB compatible	No
----------------	----

Input

Input Frequency	40 - 70 Hz auto-sensing
-----------------	-------------------------

Number of input connectors	1 Hard Wire 3-wire (2PH + G)
----------------------------	------------------------------

Efficiency at full load	160...280 V
-------------------------	-------------

Maximum Input Current per Phase	83 A
---------------------------------	------

Switching current capacity	100 A
----------------------------	-------

Input Total Harmonic Distortion	Less than 5% for full load
---------------------------------	----------------------------

Input Power Factor at Full Load	0.95
---------------------------------	------

Output

Max Configurable Power (Watts)	12000 W
--------------------------------	---------

Harmonic distortion	Less than 5%
---------------------	--------------

Output Frequency (sync to mains)	50/60 Hz +/- 3 Hz user adjustable +/- 0.1 sync to mains
----------------------------------	---

Crest factor	3 : 1
--------------	-------

Topology	Double Conversion Online
----------	--------------------------

Waveform Type	Sine wave
---------------	-----------

Overload Operation	60 seconds @ 125% and 30 seconds @ 150%
--------------------	---

Bypass type	Built-in Static Bypass Internal Bypass (Automatic and Manual) Optional External Bypass 93 % in battery operation)
-------------	--

Maximum configurable power in VA	15000 VA
----------------------------------	----------

Conformance

Product Certifications	UL 1778
------------------------	---------

Environmental

Ambient air temperature for operation	32...104 °F (0...40 °C)
---------------------------------------	-------------------------

Relative Humidity	0...95 % non-condensing
-------------------	-------------------------

Operating altitude	0...10000 ft
--------------------	--------------

Ambient Air Temperature for Storage	5...113 °F (-15...45 °C)
-------------------------------------	--------------------------

Storage Relative Humidity	0...95 % non-condensing
---------------------------	-------------------------

Storage altitude	0...50000 ft (0.00...15240.00 m)
------------------	----------------------------------

Acoustic level	50 dBA
----------------	--------

Heat dissipation	2610 Btu/h
------------------	------------

IP degree of protection	IP20
-------------------------	------

Communications & Management

Free slots	0
------------	---

Pre-Installed SmartSlot™ Cards	Network management card 2 with environmental monitoring
--------------------------------	---

Emergency Power Off (EPO)	Yes
---------------------------	-----

Surge Protection and Filtering

Filtering	Full time multi-pole noise filtering : 0.3% IEEE surge let-through : zero clamping response time : m
-----------	--

Ordering and shipping details

GTIN	731304634638
------	--------------

Packing Units

Unit Type of Package 1	PCE
------------------------	-----

Number of Units in Package 1	1
------------------------------	---

Package 1 Height	48.98 in (124.4 cm)
------------------	---------------------

Package 1 Width	39.49 in (100.3 cm)
-----------------	---------------------

Package 1 Length	24.02 in (61 cm)
------------------	------------------

Package 1 Weight	802.68 lb(US) (364.09 kg)
------------------	---------------------------

Offer Sustainability

Sustainable offer status	Green Premium product
--------------------------	-----------------------

California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
---------------------------	---

REACH Regulation	REACH Declaration
------------------	-----------------------------------

EU RoHS Directive	Compliant EU RoHS Declaration
-------------------	--

Mercury free	Yes
--------------	-----

RoHS exemption information	Yes
----------------------------	---------------------

Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information
Optimized Energy Efficiency	Energy efficient product
Take-back	Take-back program available

Contractual warranty

Warranty	2 years repair or replace
-----------------	---------------------------

Recommended replacement(s)