

# Product data sheet

Specifications



## APC Smart-UPS RT 15kVA, 208V, LCD, rackmount, 12U, 4x NEMA L6-20R & 2x NEMA L6-30R outlets

SURT15KRMXLT

### Overview

Lead time Usually Ships within 2 Weeks

### Main

Main Input Voltage	208 V
Other Input Voltage	240 V
Main Output Voltage	208 V
Other Output Voltage	240 V
Kw Rating	12000 W
Rated power in VA	15000 VA
Output connection type	4 NEMA L6-20R 2 NEMA L6-30R
Output connector type	Hard Wire 3-wire (2PH + G) 1
Number of rack unit	12U
Battery type	Lead-Acid battery
Provided equipment	CD with software Rack Mounting support rails Smart UPS signalling RS-232 cable User Manual Web/SNMP Management Card

### Batteries & Runtime

Included Battery Modules	4
Battery Slots Empty	0
Typical recharge time	2 h
RBC Quantity	4
Additional information	Configurable for 208 or 240 nominal output voltage
Battery voltage	+/-192 V (split battery referenced to neutral)
End of Discharge Battery Voltage	+/-154 V
Battery Charge Power (Watts)	1910 W rated
Battery power in VAh	3840 VAh runtime
Battery Life	3...5 year(s)
Replacement battery	<a href="#">APCRBC140</a>

<b>Battery option</b>	SURT192RMXLBP2 1 7680 VAh SURT192RMXLBP2 2 11520 VAh SURT192RMXLBP2 3 15360 VAh SURT192RMXLBP2 4 19200 VAh SURT192RMXLBP2 5 23040 VAh SURT192RMXLBP2 6 26880 VAh SURT192RMXLBP2 8 34560 VAh SURT192RMXLBP2 9 38400 VAh
-----------------------	---

<b>Extendable Run Time</b>	1
----------------------------	---

## General

<b>Number of power module free slots</b>	0
--	---

<b>Number of power module filled slots</b>	0
--	---

<b>Redundant</b>	No
------------------	----

## Physical

<b>Color</b>	Black
--------------	-------

<b>Height</b>	20.98 in (53.3 cm)
---------------	--------------------

<b>Width</b>	17.01 in (43.2 cm)
--------------	--------------------

<b>Depth</b>	30.43 in (77.3 cm)
--------------	--------------------

<b>Net Weight</b>	546.15 lb(US) (247.73 kg)
-------------------	---------------------------

<b>Mounting Location</b>	Front
--------------------------	-------

<b>Mounting preference</b>	Lower
----------------------------	-------

<b>Mounting Mode</b>	Rack-mounted
----------------------	--------------

<b>Two post mountable</b>	0
---------------------------	---

<b>USB compatible</b>	No
-----------------------	----

## Input

<b>Input Frequency</b>	40 - 70 Hz auto-sensing
------------------------	-------------------------

<b>Number of input connectors</b>	1 Hard Wire 3-wire (2PH + G)
-----------------------------------	------------------------------

<b>Efficiency at full load</b>	160...280 V
--------------------------------	-------------

<b>Maximum Input Current per Phase</b>	85 A
--	------

<b>Switching current capacity</b>	100 A
-----------------------------------	-------

<b>Input Total Harmonic Distortion</b>	Less than 5% for full load
--	----------------------------

<b>Input Power Factor at Full Load</b>	0.99
--	------

## Output

<b>Max Configurable Power (Watts)</b>	12000 W
---------------------------------------	---------

<b>Harmonic distortion</b>	Less than 5%
----------------------------	--------------

<b>Output Frequency (sync to mains)</b>	50/60 Hz +/- 3 Hz user adjustable +/- 0.1 sync to mains
---	---

<b>Crest factor</b>	3 : 1
---------------------	-------

<b>Topology</b>	Double Conversion Online
-----------------	--------------------------

<b>Waveform Type</b>	Sine wave
----------------------	-----------

<b>Overload Operation</b>	60 seconds @ 125% and 30 seconds @ 150%
---------------------------	---

<b>Bypass type</b>	Built-in Static Bypass Internal Bypass (Automatic and Manual) Optional External Bypass
--------------------	--

93 % in battery operation)

---

Maximum configurable power in VA	15000 VA
----------------------------------	----------

## Conformance

---

Product Certifications	UL 1778
------------------------	---------

## Environmental

---

Ambient air temperature for operation	32...104 °F (0...40 °C)
---------------------------------------	-------------------------

---

Relative Humidity	0...95 % non-condensing
-------------------	-------------------------

---

Operating altitude	0...10000 ft
--------------------	--------------

---

Ambient Air Temperature for Storage	5...113 °F (-15...45 °C)
-------------------------------------	--------------------------

---

Storage Relative Humidity	0...95 % non-condensing
---------------------------	-------------------------

---

Storage altitude	0...50000 ft (0.00...15240.00 m)
------------------	----------------------------------

---

Acoustic level	50 dBA
----------------	--------

---

Heat dissipation	2610 Btu/h
------------------	------------

---

IP degree of protection	IP20
-------------------------	------

## Communications & Management

---

Free slots	0
------------	---

---

Pre-Installed SmartSlot™ Cards	Network management card 2 with environmental monitoring
--------------------------------	---

---

Emergency Power Off (EPO)	Yes
---------------------------	-----

## Surge Protection and Filtering

---

Filtering	Full time multi-pole noise filtering : 0.3% IEEE surge let-through : zero clamping response time : m
-----------	--

## Ordering and shipping details

---

GTIN	731304266341
------	--------------

## Packing Units

---

Unit Type of Package 1	PCE
------------------------	-----

---

Number of Units in Package 1	1
------------------------------	---

---

Package 1 Height	38.98 in (99 cm)
------------------	------------------

---

Package 1 Width	39.49 in (100.3 cm)
-----------------	---------------------

---

Package 1 Length	24.02 in (61 cm)
------------------	------------------

---

Package 1 Weight	692.45 lb(US) (314.09 kg)
------------------	---------------------------

## Offer Sustainability

---

Sustainable offer status	Green Premium product
--------------------------	-----------------------

---

California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a>
---------------------------	---

---

REACH Regulation	<a href="#">REACH Declaration</a>
------------------	-----------------------------------

---

EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
-------------------	--

---

Mercury free	Yes
--------------	-----

---

<b>RoHS exemption information</b>	<a href="#">Yes</a>
<b>Environmental Disclosure</b>	<a href="#">Product Environmental Profile</a>
<b>Circularity Profile</b>	<a href="#">End of Life Information</a>
<b>Optimized Energy Efficiency</b>	Energy efficient product
<b>Take-back</b>	Take-back program available

---

### **Contractual warranty**

---

<b>Warranty</b>	2 years repair or replace
-----------------	---------------------------

### **Recommended replacement(s)**