


Product data sheet

Specifications



APC Smart-UPS, Line Interactive, 1500VA, Lithium-ion, Rackmount 3U, 120V, 6x NEMA 5-15R outlets, SmartConnect Port+Network Card, Short Depth, AVR, LCD

SMTL1500RM3UCNC

Overview

Lead time Usually Ships within 2 Weeks

Main

Main Input Voltage	120 V
Other Input Voltage	110 V 125 V
Main Output Voltage	120 V
Other Output Voltage	110 V 125 V
Kw Rating	1350 W
Rated power in VA	1440 VA
Input Connection Type	NEMA 5-15P
Output connection type	6 NEMA 5-15R
Number of rack unit	3U
Cable length	8 ft (2.44 m)
Battery type	Li-Ion (Lithium Ion)
Provided equipment	Rack Mounting brackets Rack Mounting support rails Screw Washer USB cable Ethernet patch cable

Complementary

Software package SmartConnect software for remote power monitoring feature availability varies by terms of use

Batteries & Runtime

Battery graph comments	This graph is based on actual measured runtime data. All measurements were taken with new, fully charged batteries and a balanced resistive load (PF = 1.0). Actual runtimes may vary from the values of this graph. Actual runtimes are dependent on several variables including battery age, battery charge level, environmental conditions and characteristics of the connected load.
Extendable Run Time	0
Typical recharge time	3 h
Battery design life	8...10 year(s)
Battery power in VAh	164 VAh runtime

Battery Charge Power (Watts)	108 W rated
------------------------------	-------------

General

Product web sub-family	Cloud-enabled monitoring
------------------------	--------------------------

Redundant	No
-----------	----

Physical

Color	Black with silver front bezel
-------	-------------------------------

Height	5.16 in (13.1 cm)
--------	-------------------

Width	17.24 in (43.8 cm)
-------	--------------------

Depth	11.89 in (30.2 cm)
-------	--------------------

Net Weight	42.99 lb(US) (19.5 kg)
------------	------------------------

Mounting preference	No preference
---------------------	---------------

Mounting Mode	Rack-mounted
---------------	--------------

USB compatible	Yes
----------------	-----

Input

Input protection type	Circuit breaker
-----------------------	-----------------

Efficiency at full load	75...154 V adjustable 82...144 V
-------------------------	-------------------------------------

Input Frequency	50/60 Hz +/- 3 Hz auto-sensing
-----------------	--------------------------------

Output

Crest factor	3 : 1
--------------	-------

Harmonic distortion	Less than 5%
---------------------	--------------

Maximum configurable power in VA	1440 VA
----------------------------------	---------

Max Configurable Power (Watts)	1350 W
--------------------------------	--------

Transfer Time	6ms typical : 10ms maximum
---------------	----------------------------

Topology	Line Interactive
----------	------------------

Waveform Type	Sine wave
---------------	-----------

Output Frequency (sync to mains)	50/60 Hz +/- 3 Hz sync to mains
----------------------------------	---------------------------------

Conformance

Product Certifications	NOM
------------------------	-----

Equipment protection policy	Lifetime : \$150000
-----------------------------	---------------------

Environmental

Acoustic level	45 dBA
----------------	--------

Heat dissipation	135 Btu/h
------------------	-----------

Operating altitude	0...10000 ft
--------------------	--------------

Ambient air temperature for operation	32...104 °F (0...40 °C)
---------------------------------------	-------------------------

Ambient Air Temperature for Storage	5...113 °F (-15...45 °C)
-------------------------------------	--------------------------

Storage altitude	0...25000 ft (0.00...7620.00 m)
------------------	---------------------------------

IP degree of protection	IP20
Relative Humidity	0...95 % non-condensing
Storage Relative Humidity	0...95 % non-condensing

Communications & Management

Alarm	Audible and visible alarms
Control panel	Multi-function LCD status and control console
Emergency Power Off (EPO)	Yes
Free slots	1
Pre-Installed SmartSlot™ Cards	Network management card with environmental monitoring
Communication port support	SmartConnect Ethernet port: for cloud monitoring feature availability varies by terms of use
Alarm	Alarm when on battery : distinctive low battery alarm

Surge Protection and Filtering

Surge energy rating	680 J
Filtering	Full time multi-pole noise filtering : 0.3% IEEE surge let-through : zero clamping response time : m

Ordering and shipping details

GTIN	731304435471
------	--------------

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1

Offer Sustainability

REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information.
RoHS exemption information	Yes
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.

Contractual warranty

Warranty	5 year repair or replace
----------	--------------------------

Recommended replacement(s)