

Product data sheet

Specifications



APC Smart-UPS, Line Interactive, 3kVA, Lithium-ion, Rackmount 2U, 120V, 2x NEMA 5-20R+6x NEMA 5-15R outlets, SmartConnect Port +SmartSlot, AVR, LCD

SMTL3000RM2UC

Overview

Lead time Usually in Stock

Main

Main Input Voltage	120 V
Other Input Voltage	110 V 125 V
Main Output Voltage	120 V
Other Output Voltage	110 V 125 V
Kw Rating	2700 W
Rated power in VA	2880 VA
Input Connection Type	NEMA L5-30P
Output connection type	2 NEMA 5-20R 6 NEMA 5-15R
Number of rack unit	2U
Cable length	8 ft (2.44 m)
Battery type	Li-Ion (Lithium Ion)
Provided equipment	Rack Mounting brackets Rack Mounting support rails Screw Washer USB cable Ethernet patch cable

Complementary

Software package SmartConnect software for remote power monitoring feature availability varies by terms of use

Batteries & Runtime

Battery graph comments This graph is based on actual measured runtime data. All measurements were taken with new, fully charged batteries and a balanced resistive load (PF = 1.0). Actual runtimes may vary from the values of this graph. Actual runtimes are dependent on several variables including battery age, battery charge level, environmental conditions and characteristics of the connected load.

Extendable Run Time	0
Typical recharge time	2 h
RBC Quantity	1

Battery design life	8...10 year(s)
Battery power in VAH	336 VAh runtime
Battery Charge Power (Watts)	216 W rated

General

Product web sub-family	Cloud-enabled monitoring
Redundant	No

Physical

Color	Black with silver front bezel
Height	3.39 in (8.6 cm)
Width	17.01 in (43.2 cm)
Depth	26.89 in (68.3 cm)
Net Weight	75.44 lb(US) (34.22 kg)
Mounting preference	Lower
Mounting Mode	Rack-mounted
USB compatible	Yes

Input

Input protection type	Circuit breaker
Efficiency at full load	82...144 V
Input Frequency	50/60 Hz +/- 3 Hz auto-sensing

Output

Crest factor	3 : 1
Harmonic distortion	Less than 5%
Maximum configurable power in VA	3000 VA
Max Configurable Power (Watts)	2700 W
Transfer Time	6ms typical : 10ms maximum
Topology	Line Interactive
Waveform Type	Sine wave
Output Frequency (sync to mains)	50/60 Hz +/- 3 Hz sync to mains

Conformance

Product Certifications	cULus ENERGY STAR V2.0 (USA)
Equipment protection policy	Lifetime : \$150000

Environmental

Acoustic level	55 dB
Heat dissipation	348 Btu/h
Operating altitude	0...10000 ft
Ambient air temperature for operation	32...104 °F (0...40 °C)

Ambient Air Temperature for Storage	5...113 °F (-15...45 °C)
Storage altitude	0...25000 ft (0.00...7620.00 m)
IP degree of protection	IP20
Relative Humidity	0...95 % non-condensing
Storage Relative Humidity	0...95 % non-condensing

Communications & Management

Alarm	Audible and visible alarms
Control panel	Multi-function LCD status and control console
Emergency Power Off (EPO)	Yes
Free slots	1
Communication port support	SmartConnect Ethernet port: for cloud monitoring feature availability varies by terms of use
Alarm	Alarm when on battery : distinctive low battery alarm

Surge Protection and Filtering

Surge energy rating	459 J
---------------------	-------

Ordering and shipping details

GTIN	731304429081
------	--------------

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	10.00 in (254 mm)
Package 1 Width	38.58 in (980 mm)
Package 1 Length	23.62 in (600 mm)
Package 1 Weight	94.05 lb(US) (42.66 kg)

Offer Sustainability

REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
RoHS exemption information	Yes
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.

Contractual warranty

Warranty	5 year repair or replace
----------	--------------------------

Recommended replacement(s)