

Product data sheet

Specifications



APC Smart-UPS X, Line Interactive, 2000VA, Rack/tower 4U, 100V-127V, 6x 5-15R+3x 5-20R+1x L5-20R NEMA, SmartSlot, Extended runtime, Short depth, TAA

SMX2000LVUS

Product availability : Stock - Normally stocked in distribution facility

Overview


Lead time Usually Ships within 2 Weeks

Main

Main Input Voltage	120 V
Other Input Voltage	100 V 110 V 127 V
Main Output Voltage	120 V
Other Output Voltage	100 V 110 V 127 V
Kw Rating	1800 W
Rated power in VA	1920 VA
Input Connection Type	NEMA 5-20P
Output connection type	6 NEMA 5-15R 3 NEMA 5-20R 1 NEMA L5-20R
Number of rack unit	4U
Cable length	8 ft (2.44 m)
Number of cables	1
Battery type	Lead-Acid battery
Provided equipment	CD with software Documentation CD Installation guide Rack mounting hardware Rack Mounting brackets Rack Mounting support rails Removable support feet Smart UPS signalling RS-232 cable USB cable

Batteries & Runtime

Extendable Run Time	1
Included Battery Modules	0
Battery Slots Empty	0

Typical recharge time	3 h
RBC Quantity	1
Battery Life	3...5 year(s)
Replacement battery	APCRBC143US 
Battery power in VAh	690 VAh runtime
Battery Charge Power (Watts)	229 W rated
Battery option	SMX120BP 1 2070 VAh SMX120BP 2 3450 VAh SMX120BP 3 4830 VAh SMX120BP 4 6210 VAh SMX120BP 6 8970 VAh SMX120BP 8 11730 VAh SMX120BP 10 14490 VAh

General

Number of power module	1750
Number of power module filled slots	0
Number of power module free slots	0
Product web sub-family	TAA compliance
Redundant	No

Physical

Color	Black
Height	17.01 in (43.2 cm)
Width	7.01 in (17.8 cm)
Depth	19.02 in (48.3 cm)
Net Weight	85.19 lb(US) (38.64 kg)
Mounting Location	Front
Mounting preference	Lower
Mounting Mode	Rack-mounted
Two post mountable	1
USB compatible	Yes

Input

Efficiency at full load	75...154 V adjustable 70...153 V
Input Frequency	50/60 Hz +/- 3 Hz auto-sensing

Output

Harmonic distortion	Less than 5%
Maximum configurable power in VA	1920 VA
Max Configurable Power (Watts)	1800 W
Transfer Time	2-4 ms 4ms typical : 8ms maximum
Topology	Line Interactive
Waveform Type	Sine wave

Output Frequency (sync to mains)	50/60 Hz +/- 3 Hz sync to mains
----------------------------------	---------------------------------

Conformance

Product Certifications	BSMI CSA NOM TAA compliance TÜV VCCI Class A
------------------------	---

Equipment protection policy	Lifetime : \$150000
-----------------------------	---------------------

Environmental

Acoustic level	55 dBA
----------------	--------

Heat dissipation	203 Btu/h
------------------	-----------

Operating altitude	0...10000 ft
--------------------	--------------

Ambient air temperature for operation	32...104 °F (0...40 °C)
---------------------------------------	-------------------------

Ambient Air Temperature for Storage	5...113 °F (-15...45 °C)
-------------------------------------	--------------------------

Storage altitude	0...50000 ft (0.00...15240.00 m)
------------------	----------------------------------

Relative Humidity	0...95 %
-------------------	----------

Storage Relative Humidity	0...95 %
---------------------------	----------

Communications & Management

Control panel	Multi-function LCD status and control console
---------------	---

Emergency Power Off (EPO)	Yes
---------------------------	-----

Free slots	1
------------	---

Control panel	LED status display with on line : on battery : replace battery and overload indicators
---------------	--

Alarm	Alarm when on battery : distinctive low battery alarm : configurable delays
-------	---

Surge Protection and Filtering

Surge energy rating	540 J
---------------------	-------

Filtering	Full time multi-pole noise filtering : 0.3% IEEE surge let-through : zero clamping response time : m
-----------	--

Ordering and shipping details

Category	80230-IG SEBA TO SEUSA
----------	------------------------

Discount Schedule	BMS1
-------------------	------

GTIN	731304340362
------	--------------

Returnability	No
---------------	----

Country of origin	PH
-------------------	----

Packing Units

Unit Type of Package 1	PCE
------------------------	-----

Number of Units in Package 1	1
------------------------------	---

Package 1 Height	12.99 in (33 cm)
------------------	------------------

Package 1 Width	24.92 in (63.3 cm)
-----------------	--------------------

Package 1 Length	23.07 in (58.6 cm)
------------------	--------------------

Package 1 Weight	105.23 lb(US) (47.73 kg)
------------------	--------------------------

Pallet unit layers	2
Pallet layers	4

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information
Optimized Energy Efficiency	Energy efficient product
Take-back	Take-back program available

Contractual warranty

Warranty	3 years repair or replace (excluding battery) and 2 years for battery, optional on-site warranties available, optional extended warranties available
----------	--

Recommended replacement(s)