


HD-TVI Dual Voltage Indoor Dome Camera with Built-In IR LEDs

HLED33DTB 2.8-12mm auto iris varifocal lens, black housing
HLED33DTW 2.8-12mm auto iris varifocal lens, white housing



Features

- Full HD resolution over coax @ 30FPS
- IR Range: 65'
- Smart DNR reduces noise in low light
- Smart IR reduces saturation of objects within close proximity to IR LEDs
- 3-axis design, both wall and ceiling mountable
- Digital wide dynamic range
- OSD for camera setting adjustments
- 12VDC/24VAC dual voltage operation
- 5 year warranty
- Additional analog output for 960 H

Specifications

Image Sensor 1/3" progressive scan CMOS 2 MP
 Resolution..... 1920 x 1080
 Minimum Illumination..... 0 lux with IR on
 S/N Ratio 50dB
 Effective Pixels 1984 (H) x 1105 (V)
 Total Pixels 2000 (H) x 1121 (V)
 Shutter 1/30 sec – 1/300,000 sec
 Number of IR LEDs 24
 IR Range 65 ft. (depending on scene reflection)
 OSD..... Yes
 Synchronization Internal
 Privacy..... On / Off (8 zones)
 Motion Detection..... On / Off (4 zones)
 Mirror On / Off

DNR..... High / Middle / Low / Off
 White Balance ATW / Push / Manual
 Image..... BLC / HLC / D-WDR / Defog
 AGC..... Level adjustable (0-20)
 TV System..... NTSC
 Housing High impact ABS
 Operating Temperature.. 14° F - 122° F
 Power Supply 12VDC, 24VAC (power supply not included)
 Power Consumption 350mA
 Dimensions..... 4.4" (Dia.) x 3.4" (H)
 Weight 8 oz.
 Included in Package Main unit, mounting screws, test monitor lead, DC lead, user manual

NDAA
COMPLIANT

*Products are in compliance with NDAA Section 889 Part B Guidelines

Optional Accessories



PSW4
24VAC
Power Supply



PSW5
12VDC
Power Supply



TVIUTPPT
HD Video
Transceiver with
Pigtail (Balun)



TVIUTP
HD Video
Transceiver