

HTB5TG

2.8mm fixed lens, dark gray housing



Features

- Supports up to 5MP @20FPS
- Built in high powered IR LEDs
- IR Range: 65' (depending on scene reflection)
- Digital Wide Dynamic Range
- IP66 compliant - weather resistant
- 12VDC (power supply not included)



Included Junction Box



Camera Specifications	
Image Sensor	1/2.7" 5MP CMOS Sensor (OS05A10)
Resolution	2,688 x 1,944 (5MP)
Scanning System	Progressive Scan
Total Pixels	2,688 (H) x 1,944 (V)
Field of View	H(Horizontal) : 103.4°~29.3° V(Vertical) : 54.3°~16.5°
Video Output	HD-ANALOG (TVI,AHD,CVBS)
Focal Length	2.8mm
Max. Aperture Ratio	F=2.0
Focal Control	Manual
Lens Type	Fixed
Min. Illumination	Color 0.5 Lux, BW 0.1 Lux
S/N Ratio	52dB (AGC o)
Frame Rate	20fps // 5MP, 30fps // 4MP

Video Specifications	
Day & Night	IR Cut Filter // Auto, Color, B/W, EXT
Brightness	1~20
Shutter	-
Sens UP	-
AGC (Gain Control)	0~20
WDR	D-WDR /ON /OFF
AWB	ATW/MWB
DNR	2D DNR (1~16)
Color Gain	1~16
Mirror	Default/H/V/HV
FLIP	-
Language	-
Defog	-
Motion	-
Privacy	-
IR LED	18ea High Power LED
Remote Control Interface	UTC

Operating & Unit Specifications	
Operating Temperature	14°F to 122°F
Ingress Protection	IP66
Input Voltage/Current	12V DC +10%
Power Consumption	Max. 5W
Weight	0.7lbs

NDAA COMPLIANT

*Products are in compliance with NDAAs Section 889 Part B Guidelines

Optional Accessories



PSW5
12VDC
Power Supply



TVIUTPPT
HD Video
Transceiver with
Pigtail (Balun)



TVIUTP
HD Video
Transceiver