

5MP HD-TVI Vandal Dome Camera with Included Junction Box

HTD5TG

2.8mm fixed lens, dark gray housing







Features

- Supports up to 5MP @20FPS
- Built in high powered IR LEDs
- IR Range: 65' (depending on scene reflection)
- Digital Wide Dynamic Range
- IP66 compliant weather resistant
- 12VDC (power supply not included)





Camera Specifications	
Image Sensor	1/2.7" 5MP CMOS Sensor (OS05A10)
Resolution	2,688 x 1,944 (5MP)
Scanning System	Progressive Scan
Total Pixels	2,688 (H) x 1,944 (V)
Field of View	H(Horizontal) : 103.4°~29.3° V(Vertical) : 54.3°~16.5°
Video Output	HD-ANALOG (TVI,AHD,CVBS)
Focal Length	2.8mm
Max. Aperture Ratio	F=2.0
Focal Control	Manual
	F: 1

Total Pixels	2,688 (H) x 1,944 (V)
Field of View	H(Horizontal) : 103.4°~29.3° V(Vertical) : 54.3°~16.5°
Video Output	HD-ANALOG (TVI,AHD,CVBS)
Focal Length	2.8mm
Max. Aperture Ratio	F=2.0
Focal Control	Manual
Lens Type	Fixed
Lens Type Min. Illumination	Fixed Color 0.5 Lux, BW 0.1 Lux
**	

Video Specifications	
Day & Night	IR Cut Filter // Auto, Color, B/W, EXT
Brightness	1~20
Shutter	-
Sens UP	-
AGC (Gain Control)	0~20
WDR	D-WDR /ON /OFF
AWB	ATW/MWB
DNR	2D DNR (1~16)
Color Gain	1~16
Mirror	Default/H/V/HV
FLIP	-
Language	-
Defog	-
Motion	-
Privacy	-
IR LED	6ea High Power LED
Remote Control Interface	UTC

Operating & Unit Specification:

Operating Temperature	14°F to 122°F
Ingress Protection	IP66
Input Voltage/Current	12V DC +10%
Power Consumption	Max. 5W
Weight	0.7lbs



*Products are in compliance with NDAA Section 889 Part B Guidelines

Optional Accessories







TVIUTPPT HD Video Transceiver with Pigtail (Balun)



TVIUTP HD Video Transceiver

Store is a service mark of Apple Inc. Android, Google Play and the Google Play logo are trademarks of Google Inc. Speco Technologies is constantly developing and improving products. We reserve the right to modify product design and specifications without notice and without incurring any obligation. Spec Rev. 7/27/23







