



2MP H.265 Facial Recognition IP Bullet Camera with Junction Box

O2BFRM

7-22mm motorized lens, white housing



Features

- Supports up to 2MP @ 30fps
- Built-in standard PoE (IEEE 802.3af)
- Built-in Face Detection and Recognition*
- Face Recognition Search with compatible Speco Recorder
- Built-in white LED for optimum face capture
- Built-in Analytics for object detection and line crossing
- H.265/H.264/MJPEG compression supported
- Built-in MicroSD slot up to 128GB (card not included)
- IP67 compliant, weather resistant
- Conformant with ONVIF Profile S
- Two-way audio
- Junction box included (works with NPT/BSP specifications)
- 5 year warranty

*Must use with N32NRE for Facial Recognition



Included Junction Box



Camera Specifications

Image Sensor	Progressive scan 1/2.8" CMOS, 2MP
Maximum Resolution	1920 x 1080
Field of View (H)	37° - 22.5°
Recommended Capture Distance	5-20ft
3-axis Adjustment	Pan: 0° - 360°, Tilt: 0° - 90°, Rotate: 0° - 360°
Minimum Illumination	F1.4, 0 lux (White LED On)
White Balance	Auto, Indoor, Outdoor, Manual
Compensation	WDR, BLC, HLC
Electronic Shutter Speed	1/25 ~ 1/100000 sec
DNR	3D

Video Specifications

Main Resolution	1080P (1920x1080) / 720P (1280x720) @ 30fps
Compression	H.265+/H.265/H.264+/H.264/MJPEG
Bitrate Control	VBR, CBR
Multiple Streaming	3 streams

Audio Specifications

Audio	1 ch input and output
-------	-----------------------

External Terminal Specifications

Ethernet	10/100 Mbps
Power	DC jack
Analog Video Output	CVBS video output (BNC x 1)
Microphone Input	3.5mm
Storage	Built-in micro SD card slot, up to 128GB

Network Specifications

Protocols	IPv4, IPv6, UDP, DHCP, NTP, RTSP, PPPoE, DDNS, SMTP, FTP, SNMP, 802.1x, UPnP, HTTPs, QoS
DDNS support	Speco DDNS (free of charge)
Security	User ID & Password protection, IP/MAC address filtering, digest authentication
User Access	Max. 6 simultaneous users. Actual number of users may vary depending on bandwidth

System Specifications

PoE	Standard (IEEE 802.3af)
Analytics	*Face Detection and Recognition, Motion detection, object removal, abnormality, line crossing, intrusion
Alarm Triggers	Analytics, sensor
Alarm Events	FTP upload, email upload
Image Settings	Privacy mask, region of interest, OSD

Client Specifications

Web Browser Support	Windows (Internet Explorer 8 and up)
PC Application	SecureGuard® VMS
Mobile	SecureGuard® Client (iPhone® and Android™)
Other Viewing Platforms	Apple TV and Amazon Fire TV

Operating & Unit Specifications

Power	PoE, 12VDC (power supply not included)
Power Consumption	12W (max)
Operating Temperature	-22°F - 140°F
Operating Humidity	Less than 95% (non-condensing)
Unit Dimensions	3.9" (Φ) x 11.0" (H)
Unit Weight	2.3 lbs



Optional Accessories



ONVIF® is a trademark of Onvif, Inc. Chrome and Firefox use Java which requires an initial internet connection. Apple and the Apple logo are trademarks of Apple Inc., registered in the U.S. and other countries. App Store is a service mark of Apple Inc. Android, Google Play and the Google Play logo are trademarks of Google Inc. Amazon's trademark is used under license from Amazon.com, Inc. or its affiliates. Speco Technologies is constantly developing and improving products. We reserve the right to modify product design and specifications without notice and without incurring any obligation. Spec Rev. 1/4/22