



Symmetra PX 40KW Extended Run Battery Frame with 8 Battery Modules & Startup

SYCFXR8-8

Ov	er	VI	e	W
----	----	----	---	---

Lead time Usually in Stock

Main	
Main Input Voltage	208 V 3 phase
Number of cables	1
Battery Type	VRLA
Provided Equipment	Installation guide Start-Up Service User Manual

Batteries & Runtime

Battery Placement	Battery Cabinet
Battery blocks per string	32
Battery Slots Empty	0
Included Battery Modules	8
Battery manufacturer	Panasonic
Device mounting	Enclosed battery cabinet
Battery Voltage	192V

Physical

Color	Black
Height	81.50 in (207 cm)
Width	22.99 in (58.4 cm)
Depth	35.51 in (90.2 cm)
Net Weight	2171.56 lb(US) (985 kg)

Input

Input Frequency	50/60 Hz +/- 5 Hz auto sensing
Number of input connectors	1 Hard Wire 4-wire (3PH + G)

Conformance

Product Certifications	Eurobat General Purpose

Environmental

Ambient Air Temperature for Operation	32104 °F (040 °C)
Operating altitude	03333 ft
Relative Humidity	095 %
Ambient Air Temperature for Storage	5113 °F (-1545 °C)
Storage Relative Humidity	095 %

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	90.98 in (231.1 cm)
Package 1 Width	40.00 in (101.6 cm)
Package 1 Length	30.00 in (76.2 cm)
Package 1 Weight	2204.62 lb(US) (1000 kg)

Offer Sustainability

Sustainable offer status	Green Premium product
REACh Regulation	REACh Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Lead free	Yes
Take-back	Take-back program available

Contractual warranty

Contractual warranty	
Warranty	1 year repair or replace

Recommended replacement(s)