

Product data sheet

Specifications



Symmetra PX 125kW Scalable to 250kW w/o Bypass, Distribution or Batteries-Parallel Capable

SY125K250D-NB

Overview

Presentation A high-performance, 3-phase, modular, scalable, power protection solution with industry-leading efficiency, capacity, and performance for medium to large data centers and mission-critical environments. Multiple UPSs can be installed in parallel for ultra-efficient system redundancy or up to 2MW of power protection. Parallel installations with custom switchgear and installations using a 3rd-party maintenance bypass panel require the APC Symmetra PX250/500 Third Party Switchgear Kit for breaker monitoring and EPO functionality.

Lead time Usually Ships within 6 Weeks

Main

Main Input Voltage 480 V 3 phase
400 V 3 phase

Other Input Voltage 415 V

Main Output Voltage 480 V 3 phase
400 V 3 phase

Other Output Voltage 415 V

Kw Rating 125000 W

Rated power in VA 125000 VA

Output connector type Hard Wire 4-wire (3PH + G) 1
Hard Wire 5-wire (3PH + N + G) 1

Battery Type External battery system

Provided equipment Assembly service
Installation guide
Network Management Card
Start-Up Service
User Manual

Batteries & Runtime

Battery Slots Empty 0

Battery power in VAh 0 VAh runtime

Extendable Run Time 1

General

Bypass Voltage Tolerance +/-10% settable from +/-4/6/8 and 10%

Number of power module free slots 5

Number of power module filled slots 5

Redundant	Yes
-----------	-----

Physical

Color	Black
Height	78.39 in (199.1 cm)
Width	47.24 in (120 cm)
Depth	42.13 in (107 cm)
Net Weight	1904.80 lb(US) (864 kg)
USB compatible	No

Input

Input Frequency	40 - 70 Hz auto-sensing
Number of input connectors	1 Hard Wire 4-wire (3PH + G) 1 Hard Wire 5-wire (3PH + N + G)
Efficiency at full load	408...552 V 480 V
Maximum Short Circuit Withstand (Icw)	50 kA
Input Total Harmonic Distortion	Less than 5% for full load
Input protection type	3-pole breaker
Load power factor	0.5 leading to 0.5 lagging
Input Power Factor at Full Load	0.99

Output

Max Configurable Power (Watts)	250000 W
Harmonic distortion	Less than 2%
Output Frequency (sync to mains)	50 Hz sync to mains 60 Hz +/- 0.1 % for 60 Hz nominal not synced 50 Hz +/- 0.1 % for 50 Hz nominal not synced 60 Hz sync to mains
Topology	Double Conversion Online
Waveform Type	Sine wave
Output voltage tolerance	+/-1% static and +/- 5% at 100% load step
Output Voltage THD	< 2% linear load and < 3% non-linear load
Overload Operation	10 minutes @ 125% and 60 seconds @ 150%
Bypass type	Built-in Static Bypass 96 % in battery operation)
Maximum configurable power in VA	500000 VA
Transfer Time	2ms typical

Conformance

Product Certifications	cUL Listed UL Listed
Standards	CSA C22.2 No.107.3-05 EN/IEC 62040-1-1 EN/IEC 62040-2 EN/IEC 62040-3 OSHDP UL 1778 UL 60950-1

Environmental

Ambient Air Temperature for Operation	32...104 °F (0...40 °C)
Relative Humidity	0...95 %
Operating altitude	0...3333 ft
Ambient Air Temperature for Storage	-22...158 °F (-30...70 °C)
Storage Relative Humidity	0...95 %
Storage altitude	0...50000 ft (0.00...15240.00 m)
Acoustic level	54 dBA
Heat dissipation	15473 Btu/h
NEMA degree of protection	NEMA 1
IP degree of protection	IP20

Communications & Management

Free slots	1
Pre-Installed SmartSlot™ Cards	Network management card 2 with environmental monitoring, out of band access and Modbus
Control panel	Touch Screen LCD User Interface
Emergency Power Off (EPO)	Optional

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	84.65 in (215 cm)
Package 1 Width	50.00 in (127 cm)
Package 1 Length	73.62 in (187 cm)
Package 1 Weight	2204.62 lb(US) (1000 kg)

Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
EU RoHS Directive	Compliant EU RoHS Declaration
China RoHS Regulation	China RoHS declaration
RoHS exemption information	Yes
Optimized Energy Efficiency	Energy efficient product

Contractual warranty

Warranty	1 year on-site repair or replace with factory authorized Start-Up
----------	---

Recommended replacement(s)