

# Product data sheet

Specifications



## APC Symmetra LX 12kVA Scalable to 16kVA N+1 Ext. Run Tower, 208/240V

SYA12K16PXR

### Overview

Lead time Usually in Stock

### Main

Main Input Voltage	208 V
Other Input Voltage	240 V
Main Output Voltage	120 V 208 V
Other Output Voltage	240 V
Kw Rating	9600 W
Rated power in VA	12000 VA
Output connector type	Hard Wire 4-wire (2PH+N+G) 1
Battery type	Lead-Acid battery
Provided equipment	CD with software Documentation CD Installation guide User Manual Web/SNMP Management Card

### Batteries & Runtime

Included Battery Modules	9
Battery Slots Empty	4
Typical recharge time	7.5 h
Additional information	Configurable for 120/208 or 120/240 output voltage
Battery Charge Power (Watts)	1035 W rated
Battery power in VAh	7776 VAh runtime
Battery Life	3...5 year(s)
Replacement battery	<a href="#">SYA8K16PX798</a>
	<a href="#">SYBT5</a>
Battery option	SYBT5 2 9504 VAh SYBT5 4 11232 VAh SYAXR9B9 1 15552 VAh SYAXR9B9 2 23328 VAh SYAXR9B9 3 31104 VAh SYAXR9B9 4 38880 VAh SYAXR9B9 5 46656 VAh SYAXR9B9 6 54432 VAh

Extendable Run Time	1
---------------------	---

## General

Product web sub-family	4kVA power increments
------------------------	-----------------------

Number of power module free slots	2
-----------------------------------	---

Number of power module filled slots	3
-------------------------------------	---

Redundant	Yes
-----------	-----

## Physical

Color	Black Silver
-------	-----------------

Height	59.69 in (151.6 cm)
--------	---------------------

Width	19.02 in (48.3 cm)
-------	--------------------

Depth	28.58 in (72.6 cm)
-------	--------------------

Net Weight	1077.27 lb(US) (488.64 kg)
------------	----------------------------

Mounting Location	Front
-------------------	-------

Mounting preference	No preference
---------------------	---------------

Mounting Mode	Not rack-mountable
---------------	--------------------

Two post mountable	0
--------------------	---

USB compatible	No
----------------	----

## Input

Input Frequency	45...65 Hz auto-sensing
-----------------	-------------------------

Number of input connectors	1 Hard Wire 4-wire (2PH+N+G)
----------------------------	------------------------------

Efficiency at full load	96...138 V line to neutral
-------------------------	----------------------------

Input Total Harmonic Distortion	Less than 7% for full load
---------------------------------	----------------------------

Input Power Factor at Full Load	0.98
---------------------------------	------

## Output

Max Configurable Power (Watts)	12800 W
--------------------------------	---------

Harmonic distortion	Less than 5 % at full load
---------------------	----------------------------

Output Frequency (sync to mains)	47...63 Hz sync to mains 60 Hz +/- 0.1 % for 60 Hz nominal not synced 50 Hz +/- 0.1 % for 50 Hz nominal not synced
----------------------------------	--

Crest factor	Up to 5 : 1
--------------	-------------

Topology	Double Conversion Online
----------	--------------------------

Waveform Type	Sine wave
---------------	-----------

Bypass type	Internal Bypass (Automatic and Manual) Optional External Bypass
-------------	--

Maximum output current	56 A
------------------------	------

Maximum configurable power in VA	16000 VA
----------------------------------	----------

## Conformance

Product Certifications	CSA
------------------------	-----

Standards	FCC Part 15 class A
-----------	---------------------

## Environmental

Ambient air temperature for operation	32...104 °F (0...40 °C)
Relative Humidity	0...95 %
Operating altitude	0...10000 ft
Ambient Air Temperature for Storage	5...113 °F (-15...45 °C)
Storage Relative Humidity	0...95 %
Storage altitude	0...15000 ft (0.00...4572.00 m)
Acoustic level	62 dBA
Heat dissipation	4995 Btu/h

## Communications & Management

Free slots	1
Pre-Installed SmartSlot™ Cards	Network management card 2 with environmental monitoring
Control panel	Multi-function LCD status and control console
Alarm	Audible and visible alarms : prioritized by severity
Emergency Power Off (EPO)	Yes

## Ordering and shipping details

GTIN	731304739869
------	--------------

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	74.02 in (188 cm)
Package 1 Width	39.25 in (99.7 cm)
Package 1 Length	23.58 in (59.9 cm)
Package 1 Weight	1147.42 lb(US) (520.46 kg)

## Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a>
REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
Optimized Energy Efficiency	Energy efficient product
Take-back	Take-back program available

## Contractual warranty

Warranty	2 years repair or replace
----------	---------------------------

**Recommended replacement(s)**